



H2OLOX[®]

RESIN-MODIFIED TUNG OIL EMULSION



Protect your wood project with the trusted, go-to finish wood enthusiasts choose.

Easy to apply, maintain and spot repair

Enhances wood grain, dries hard and flexible

Low odor, sustainable and eco-friendly

Available in gloss, semi-gloss, satin and matte sheens



FAMILY OWNED SINCE 1910



Learn more at waterlox.com/h2olox

Our H2OLOX® Formula

Our H2OLOX formula is emulsion-based with less solvents, making it low odor and eco-friendly. When used in conjunction with our UNIVERSAL Tung Oil Sealer, it penetrates deep into wood to lock out water and provide a rich, distinctive finish that is easy to apply, maintain and spot repair.

PRODUCT DETAILS:

- The same beauty, feel and protection of Waterlox Original.
- Low odor, eco-friendly and available for use in all 50 states, Canada and Europe. Replaces our 350 and 450 VOC compliant products.
- Like all of our Tung Oil formulas, 90% of the resin portion of the formula is from renewable, natural resources.
- When used in conjunction with the Universal Tung Oil Sealer, H2OLOX provides the same beauty, feel and protection of Waterlox Original.
- Easier to maintain and clean than other interior clear or surface finishes.
- Non-toxic when dry and fully cured. Isocyanate-free, no cross-linker and no wax.
- Handcrafted in small batches in Cleveland, Ohio by a 4th generation, family-owned company.
- Available in gloss, semi-gloss, satin and matte sheens in gallon, quart and 2 ounce sizes.

PRODUCT USES & TIPS:

- Use on interior wood surfaces including floors, windows, doors, cabinetry, woodwork, tables, furniture, countertops, picture frames and various woodworking projects.
- Because it remains elastic, it is a good choice for soft woods (like pine and reclaimed lumber). It also provides exceptional adhesion to oily, dense, exotic woods (like teak, rosewood and ipe).
- Perfect for restoration projects and period or century homes to enhance and preserve the natural character of the wood with a hand-rubbed, old-world appearance.
- One gallon of H2OLOX finish covers 500 square feet per coat (125 square feet per coat for one quart). One quart of the UNIVERSAL Tung Oil Sealer covers 600-800 square feet per coat. No thinning required.
- Minimum dry time of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.
- Keep container closed when not in use and keep from freezing.

- 1 First, apply this product to create a waterproof seal.

UNIVERSAL TUNG OIL SEALER

PRODUCT #: **TB 1000**

This product is a sealer and should be used under the Waterlox H2OLOX Finish products (TB 2000, TB 2001, TB 2002 and TB 2003).



- 2 Second, apply one of these products to build a protective and elastic finish.

H2OLOX GLOSS FINISH

PRODUCT #: **TB 2000**

GLOSS LEVEL: **75-80°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox UNIVERSAL Tung Oil Sealer (TB 1000).



H2OLOX SEMI-GLOSS FINISH

PRODUCT #: **TB 2003**

GLOSS LEVEL: **55-60°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox UNIVERSAL Tung Oil Sealer (TB 1000).



H2OLOX SATIN FINISH

PRODUCT #: **TB 2001**

GLOSS LEVEL: **30-40°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox UNIVERSAL Tung Oil Sealer (TB 1000).



H2OLOX MATTE FINISH

PRODUCT #: **TB 2002**

GLOSS LEVEL: **8-12°**

This product is a finish and should be used as the 2nd and 3rd coats over the Waterlox UNIVERSAL Tung Oil Sealer (TB 1000).



Premium tung oil finishes since 1910.