

# Product Specifications



| Product  | Product # | Sheen      | Product Use     | Vol Solids +/- 1.0% | Wt./Gal.  | Hrs. Dry Re-Coat <sup>1</sup> | VOC g/L | Coverage <sup>2</sup> Per Gal. |
|--|-----------|------------|-----------------|---------------------|-----------|-------------------------------|---------|--------------------------------|
| <b>Waterlox ORIGINAL Formula</b>                       |           |            |                 |                     |           |                               |         |                                |
| <b>Waterlox ORIGINAL Sealer/Finish</b>                 | TB 5284   | Medium     | Sealer & Finish | 22.3                | 6.95      | 24                            | 614     | 500 Sq. Ft.                    |
| <b>Waterlox ORIGINAL Satin Finish</b>                  | TB 6044   | Satin      | Finish          | 33.6                | 7.28      | 24                            | 524     | 500 Sq. Ft.                    |
| <b>Waterlox ORIGINAL High Gloss Finish</b>             | TB 3182   | High Gloss | Finish          | 34.1                | 7.18      | 24                            | 523     | 500 Sq. Ft.                    |
| <b>Waterlox ORIGINAL 350 VOC Sealer/Finish</b>         | TB 6038   | Medium     | Sealer & Finish | 27.8                | 9.35      | 24                            | 347     | 500 Sq. Ft.                    |
| <b>Waterlox ORIGINAL 350 VOC Satin Finish</b>          | TB 6035   | Satin      | Finish          | 34.3                | 9.10      | 24                            | 345     | 500 Sq. Ft.                    |
| <b>Waterlox ORIGINAL 450 VOC Satin Finish</b>          | TB 6045   | Satin      | Finish          | 36.1                | 8.25      | 24                            | 445     | 500 Sq. Ft.                    |
| <b>Waterlox MARINE Formula</b>                         |           |            |                 |                     |           |                               |         |                                |
| <b>Waterlox MARINE Sealer</b>                          | TB 3809   | Medium     | Exterior Primer | 22.3                | 6.95      | 24                            | 614     | 500 Sq. Ft.                    |
| <b>Waterlox MARINE Satin Finish</b>                    | TB 6032   | Satin      | Exterior Finish | 36.0                | 7.27      | 24                            | 508     | 500 Sq. Ft.                    |
| <b>Waterlox MARINE High Gloss Finish</b>               | TB 3940   | High Gloss | Exterior Finish | 43.6                | 7.44      | 24                            | 450     | 500 Sq. Ft.                    |
| <b>Waterlox TRUETONE Formula</b>                       |           |            |                 |                     |           |                               |         |                                |
| <b>Waterlox TRUETONE Color-Infused Tung Oil Stains</b> | Various   | Matte/Flat | Sealer/Stain    | 70-75               | 7.58-8.77 | 24                            | < 275   | 3,200-3,400 Sq. Ft.            |
| <b>Waterlox TRUETONE Buff-In Tung Oil Finish</b>       | TB 7011   | Matte/Flat | Finish          | 75.0                | 7.58      | 24                            | < 275   | 3,200-3,400 Sq. Ft.            |



<sup>1</sup> Based on adequate cross-ventilation, 70° F; and < 50% relative humidity. Review the Ventilation FAQs on our website at waterlox.com. <sup>2</sup> Suggested spread rate(s). <sup>3</sup> After 12 hours must be sanded for inter-coat adhesion. <sup>4</sup> Must be buffed for inter-coat adhesion/aesthetics\* with a 3M Maroon pad

# Product Specifications



| Product                                    | Product # | Sheen      | Product Use     | Vol Solids +/- 1.0% | Wt./Gal. | Hrs. Dry Re-Coat <sup>1</sup>            | VOC g/L | Coverage <sup>2</sup> Per Gal. |
|--|-----------|------------|-----------------|---------------------|----------|--|---------|--------------------------------|
| <b>Waterlox URETHANE Formula</b>           |           |            |                 |                     |          |  |         |                                |
| <b>Waterlox URETHANE Satin Finish</b>      | TB 5930   | Satin      | Finish          | 36.4                | 7.35     | 6 <sup>3</sup>                           | 527     | 500 Sq. Ft.                    |
| <b>Waterlox URETHANE Gloss Finish</b>      | TB 4252   | Gloss      | Finish          | 34.0                | 7.22     | 6 <sup>3</sup>                           | 547     | 500 Sq. Ft.                    |
| <b>Waterlox URETHANE Semi-Gloss Finish</b> | TB 5824   | Semi-Gloss | Finish          | 35.0                | 7.25     | 6 <sup>3</sup>                           | 541     | 500 Sq. Ft.                    |
| <b>Waterlox H2OLOX Formula</b>             |           |            |                 |                     |          |  |         |                                |
| <b>Waterlox H2OLOX Gloss Finish</b>        | TB 2000   | Gloss      | Finish          | 30.0                | 8.22     | Overnight or minimum 16 hrs <sup>4</sup> | 188     | 500 Sq. Ft.                    |
| <b>Waterlox H2OLOX Semi-Gloss Finish</b>   | TB 2003   | Semi-Gloss | Finish          | 30.0                | 8.24     | Overnight or minimum 16 hrs <sup>4</sup> | 184     | 500 Sq. Ft.                    |
| <b>Waterlox H2OLOX Satin Finish</b>        | TB 2001   | Satin      | Finish          | 30.0                | 8.25     | Overnight or minimum 16 hrs <sup>4</sup> | 185     | 500 Sq. Ft.                    |
| <b>Waterlox H2OLOX Matte Finish</b>        | TB 2002   | Matte      | Finish          | 31.0                | 8.31     | Overnight or minimum 16 hrs <sup>4</sup> | 188     | 500 Sq. Ft.                    |
| <b>Waterlox UNIVERSAL Tung Oil Sealer</b>  |           |            |                 |                     |          |  |         |                                |
| <b>UNIVERSAL Tung Oil Sealer (UTOS)</b>    | TB 1000   | Flat       | Sealer          | 87.0                | 7.77     | Overnight or minimum 16 hrs <sup>4</sup> | 99      | 3200 Sq. Ft.                   |
| <b>Waterlox Pure Tung Oil</b>              |           |            |                 |                     |          |  |         |                                |
| <b>Waterlox Pure Tung Oil</b>              | TB 6050   | Matte      | Sealer & Finish | 100.0               | 7.8      | 24+                                      | 0       | 4,000 Sq. Ft.                  |



<sup>1</sup> Based on adequate cross-ventilation, 70° F; and < 50% relative humidity. Review the Ventilation FAQs on our website at waterlox.com. <sup>2</sup> Suggested spread rate(s). <sup>3</sup> After 12 hours must be sanded for inter-coat adhesion. <sup>4</sup> Must be buffed for inter-coat adhesion/aesthetics\* with a 3M Maroon pad