

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

1 Identification

- **Product identifier**
- **Trade name:** Marine Finish Satin Sheen
- **Article number:** TB 6032
- **Recommended use and restriction on use**
- **Recommended use:** Coating compound/ Surface coating/ paint
- **Restrictions on use:** No further relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Waterlox Coatings Corporation
9808 Meech Avenue
CLEVELAND, OH 44105
(216) 641-4877
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Additional information:**

There are no other hazards not otherwise classified that have been identified.
0 percent of the mixture consists of ingredient(s) of unknown toxicity.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS05 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent
 phthalic anhydride
 Distillates (petroleum), hydrotreated light
 Pine Oil
 Naphthenic acids, cobalt salts
 2-butanone oxime

- **Hazard statements**

H226 Flammable liquid and vapor.
 H318 Causes serious eye damage.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H361 Suspected of damaging fertility or the unborn child.
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.
 P260 Do not breathe mist/vapors/spray.
 P284 In case of inadequate ventilation wear respiratory protection.
 P264 Wash thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection.
 P233 Keep container tightly closed.
 P270 Do not eat, drink or smoke when using this product.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
 P363 Wash contaminated clothing before reuse.
 P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P331 Do NOT induce vomiting.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



Warning: Contains lead salt(s). Long-term health hazard.

* - Indicates a long term health hazard from repeated or prolonged exposures.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|------------|---|---------|
| 8052-41-3 | Stoddard solvent | 25-50% |
| | <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 1, H372; Asp. Tox. 1, H304 | |
| 64742-47-8 | Distillates (petroleum), hydrotreated light | 10-25% |
| | <ul style="list-style-type: none"> ⚠ Asp. Tox. 1, H304 | |
| 85-44-9 | phthalic anhydride | 2.5-10% |
| | <ul style="list-style-type: none"> ⚠ Resp. Sens. 1, H334 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 | |
| 1330-20-7 | xylene | 2.5-10% |
| | <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | |
| 56-81-5 | glycerol | ≤ 2.5% |
| 8002-09-3 | Pine Oil | ≤ 2.5% |
| | <ul style="list-style-type: none"> ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317 ⚠ Flam. Liq. 4, H227 | |

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 3)

| | | |
|------------|---|--------|
| 96-29-7 | 2-butanone oxime  Carc. 2, H351  Eye Dam. 1, H318  Acute Tox. 4, H312; Skin Sens. 1, H317 Flam. Liq. 4, H227 | ≤ 2.5% |
| 98-54-4 | 4-tert-butylphenol  Repr. 2, H361  Eye Dam. 1, H318  Skin Irrit. 2, H315 | ≤ 2.5% |
| 61789-51-3 | Naphthenic acids, cobalt salts  Carc. 2, H351; Repr. 2, H361  Skin Sens. 1, H317 | ≤ 2.5% |

· **Additional information:**

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air and to be sure to call for a doctor.
Provide oxygen treatment if affected person has difficulty breathing.
In case of irregular breathing or respiratory arrest provide artificial respiration.
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately remove any clothing soiled by the product.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.
Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
A person vomiting while lying on their back should be turned onto their side.
Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Asthma attacks
Headache
Breathing difficulty
Allergic reactions
Coughing
Dizziness
Nausea
Strong irritant with the danger of severe eye injury.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 4)

- **Danger**
 May cause respiratory irritation.
 Danger of impaired breathing.
 Danger of disturbed cardiac rhythm.
 Danger of convulsion.
 Vapours may cause drowsiness and dizziness.
- **Indication of any immediate medical attention and special treatment needed**
 If swallowed or in case of vomiting, danger of entering the lungs.
 Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.
 Later observation for pneumonia and pulmonary edema.
 Medical supervision for at least 48 hours.
 Monitor circulation, possible shock treatment.
 If necessary oxygen respiration treatment.
 Treat skin and mucous membrane with antihistamine and corticoid preparations.
 Contains phthalic anhydride. May produce an allergic reaction.
 In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 Foam
 Fire-extinguishing powder
 Gaseous extinguishing agents
 Carbon dioxide
 Water fog / haze
- **For safety reasons unsuitable extinguishing agents:**
 Water spray
 Water stream.
- **Special hazards arising from the substance or mixture**
 Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
 Wear self-contained respiratory protective device.
 Do not inhale explosion gases or combustion gases.
 Wear fully protective suit.
- **Additional information**
 Eliminate all ignition sources if safe to do so.
 Cool endangered receptacles with water fog.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation.
 Keep away from ignition sources.
 Protect from heat.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 5)

Isolate area and prevent access.

Particular danger of slipping on leaked/spilled product.

· **Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

· **Methods and material for containment and cleaning up:**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Allow to solidify. Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty receptacles.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizers, strong acids, strong bases.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep containers tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 6)

· Control parameters

· Components with limit values that require monitoring at the workplace:

8052-41-3 Stoddard solvent

| | |
|---------------|---|
| PEL (USA) | Long-term value: 2900 mg/m ³ , 500 ppm |
| REL (USA) | Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min |
| TLV (USA) | Long-term value: 525 mg/m ³ , 100 ppm |
| EL (Canada) | Short-term value: 580 mg/m ³ Long-term value: 290 mg/m ³ |
| EV (Canada) | Long-term value: 525 mg/m ³ |
| LMPE (Mexico) | Long-term value: 100 ppm |

64742-47-8 Distillates (petroleum), hydrotreated light

| | |
|-------------|--|
| EL (Canada) | Long-term value: 200 mg/m ³ Skin |
|-------------|--|

1330-20-7 xylene

| | |
|---------------|--|
| PEL (USA) | Long-term value: 435 mg/m ³ , 100 ppm |
| REL (USA) | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV (USA) | Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI |
| EL (Canada) | Short-term value: 150 ppm Long-term value: 100 ppm |
| EV (Canada) | Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| LMPE (Mexico) | Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE |

56-81-5 glycerol

| | |
|---------------|---|
| PEL (USA) | Long-term value: 15* 5** mg/m ³ mist; *total dust **respirable fraction |
| TLV (USA) | TLV withdrawn-insufficient data human occup. exp. |
| EL (Canada) | Long-term value: 10* 3** mg/m ³ *mist; **mist, respirable |
| EV (Canada) | Long-term value: 10 mg/m ³ |
| LMPE (Mexico) | Long-term value: 10 mg/m ³ |

96-29-7 2-butanone oxime

| | |
|------------|---------------------------------|
| WEEL (USA) | Long-term value: 10 ppm DSEN |
|------------|---------------------------------|

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 7)

· **Ingredients with biological limit values:**

1330-20-7 xylene

| | |
|-----------|--|
| BEI (USA) | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----------|--|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Pregnant women should strictly avoid inhalation or ingestion.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Engineering controls:** No further relevant information available.

· **Breathing equipment:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**

Contact lenses should not be worn.



Safety glasses

· **Body protection:** Solvent resistant protective clothing

· **Limitation and supervision of exposure into the environment**

No further relevant information available.

· **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 8)

9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Liquid

Color: Amber colored

- Odor: Petroleum-like

- Odor threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 140 - 199 °C (284 - 390 °F)

- Flash point: 35 °C (95 °F)

- Flammability (solid, gaseous): Not applicable.

- Auto-ignition temperature: Not determined.

- Decomposition temperature: Not determined.

- Auto igniting: Product is not self-igniting.

- Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- Explosion limits:

Lower: 0.8 Vol %

Upper: 7.0 Vol %

- Vapor pressure at 20 °C (68 °F): 2 hPa (2 mm Hg)

- Density at 20 °C (68 °F): 0.87 g/cm³ (7.26 lbs/gal)

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not determined.

- Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

- Partition coefficient (n-octanol/water): Not determined.

- Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

- Other information: No further relevant information available.

10 Stability and reactivity

- Reactivity: No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 9)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Avoid open flame, ignition sources, contact with incompatible substances.
- **Possibility of hazardous reactions**
Flammable.
Reacts with strong acids and oxidizing agents.
Reacts with strong alkali.
Used empty containers may contain product gases which form explosive mixtures with air.
Toxic fumes may be released if heated above the decomposition point.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrocarbons
Toxic metal compounds

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **on the skin:** Based on available data, the classification criteria are not met.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** May cause sensitisation by inhalation and skin contact.
- **Subacute to chronic toxicity:** May be fatal if swallowed and enters airways.
- **Additional toxicological information:**
- **Carcinogenic categories**

| |
|--|
| · NTP (National Toxicology Program) |
|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| |
|--|
| · OSHA-Ca (Occupational Safety & Health Administration) |
|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

- **Probable Routes of Exposure**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Acute effects (acute toxicity, irritation and corrosivity):**

May cause sensitisation by inhalation and skin contact.
Causes serious eye damage.

- **Repeated Dose Toxicity:** Repeated exposures may result in skin and/or respiratory sensitivity.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**

Carc. 2, Repr. 2

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 10)

- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Suspected of damaging fertility or the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to the central nervous system through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** The material is harmful to the environment.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 11)

- **UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

- **DOT, IATA**

Paint related material

- **ADR**

1263 PAINT RELATED MATERIAL

- **IMDG**

PAINT RELATED MATERIAL

- **Transport hazard class(es)**

- **DOT**



- **Class**

3 Flammable liquids

- **Label**

3

- **ADR**



- **Class**

3 (F1) Flammable liquids

- **Label**

3

- **IMDG, IATA**



- **Class**

3 Flammable liquids

- **Label**

3

- **Packing group**

III

- **DOT, ADR, IMDG, IATA**

- **Environmental hazards:**

- **Marine pollutant:**

No

- **Special precautions for user**

Warning: Flammable liquids

- **Danger code (Kemler):**

30

- **EMS Number:**

F-E,S-E

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **ADR**

- **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

(Contd. of page 12)

- **IMDG**
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN1263, Paint related material, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- **United States (USA)**
- **SARA**

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

| | |
|------------|--------------------------------|
| 85-44-9 | phthalic anhydride |
| 1330-20-7 | xylene |
| 61789-51-3 | Naphthenic acids, cobalt salts |

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

| | | |
|-----------|------------|---|
| 1330-20-7 | xylene | I |
| 71-36-3 | butan-1-ol | D |

· IARC (International Agency for Research on Cancer)

| | | |
|------------|---------------------------------------|----|
| 1330-20-7 | xylene | 3 |
| 9003-07-0 | polypropylene glycol diglycidyl ether | 3 |
| 61789-51-3 | Naphthenic acids, cobalt salts | 2B |

· TLV (Threshold Limit Value established by ACGIH)

| | | |
|-----------|--------------------|----|
| 85-44-9 | phthalic anhydride | A4 |
| 1330-20-7 | xylene | A4 |

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· State Right to Know Listings

None of the ingredients is listed.

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015

Reviewed on 07/09/2015

Trade name: Marine Finish Satin

- **Canadian substance listings:**

(Contd. of page 13)

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

85-44-9 | phthalic anhydride

- **Canadian Ingredient Disclosure list (limit 1%)**

8052-41-3 | Stoddard solvent

- **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 07/09/2015 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· Sources

SDS Prepared by: ChemTel Inc.

1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com