Printing date 07/09/2015 Reviewed on 07/09/2015

1 Identification

Product identifier

Trade name: Waterlox Original Sealer/Finish

Article number: TB 5284

Recommended use and restriction on use

 $\cdot \textbf{Recommended use:} \ Coating \ compound/ \ Surface \ coating/ \ paint$

• Restrictions on use: No further relevant information available.

Details of the supplier of the Safety Data Sheet

• Manufacturer/Supplier: Waterlox Coatings Corporation 9808 Meech Avenue CLEVELAND, OH 44105 (216) 641-4877

Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated

exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Additional information:

There are no other hazards not otherwise classified that have been identified. 0 percent of the mixture consists of ingredient(s) of unknown toxicity.

- Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 1)

Hazard pictograms



GHS07







GHS02 GHS07 GHS08

Signal word Danger

· Hazard-determining components of labeling:

Stoddard solvent

Naphthenic acids, cobalt salts

2-butanone oxime

Rosin

Hazard statements

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection.

P233 Keep container tightly closed.

P270 Do not eat, drink or smoke when using this product.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Classification system:

NFPA ratings (scale 0 - 4)



(Contd. on page 3)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 2)

HMIS-ratings (scale 0 - 4)



- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
8052-41-3	Stoddard solvent	 Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 	50-100%
8050-09-7	Rosin	♦ Skin Sens. 1, H317	≤ 2.5%
136-51-6	calcium bis(2-ethylhexanoate)	Repr. 2, H361 Eye Dam. 1, H318	≤ 2.5%
61789-51-3	Naphthenic acids, cobalt salts	Carc. 2, H351; Repr. 2, H361 Skin Sens. 1, H317	≤ 2.5%
96-29-7	2-butanone oxime	Carc. 2, H351 Eye Dam. 1, H318 Acute Tox. 4, H312; Skin Sens. 1, H317 Flam. Liq. 4, H227	≤ 2.5%

Additional information:

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

- Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses if worn.

(Contd. on page 4)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 3)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while lying on their back should be turned onto their side.

Do not induce vomiting; immediately call for medical help.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Headache

Breathing difficulty

Coughing

Dizziness

Nausea

Disorientation

Danger

Danger of pulmonary edema.

Danger of impaired breathing.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Vapours may cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Contains Naphthenic acids, cobalt salts, 2-butanone oxime, Rosin. May produce an allergic reaction.

Medical supervision for at least 48 hours.

Later observation for pneumonia and pulmonary edema.

Monitor circulation, possible shock treatment.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

Water fog / haze

· For safety reasons unsuitable extinguishing agents:

Water spray

Water stream.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

(Contd. on page 5)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 4)

Cool endangered receptacles with water fog.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

Particular danger of slipping on leaked/spilled product.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

· Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Remove from the water surface (e.g. skim or suck off).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
- Precautions for safe handling

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable liquid and vapor.

- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep containers tightly sealed.

(Contd. on page 6)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

· Specific end use(s) No further relevant information available.

(Contd. of page 5)

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters

· Components with limit values that require monitoring at the workplace:			
8052-41-3 Stoddard solvent			
PEL (USA)	Long-term value: 2900 mg/m³, 500 ppm		
REL (USA)	Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min		
TLV (USA)	Long-term value: 525 mg/m³, 100 ppm		
EL (Canada)	Short-term value: 580 mg/m³ Long-term value: 290 mg/m³		
EV (Canada)	Long-term value: 525 mg/m ³		
LMPE (Mexico)	Long-term value: 100 ppm		
8050-09-7 Rosin			
TLV (USA)	DSEN, RSEN, L		
EL (Canada)	S		
LMPE (Mexico)	SEN, (L)		
96-29-7 2-butanone oxime			
WEEL (USA)	Long-term value: 10 ppm DSEN		

- Additional information: The lists that were valid during the creation were used as basis.
- **Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or ingestion.

- Engineering controls: No further relevant information available.
- Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

(Contd. on page 7)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 6)

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:



Safety glasses

- Body protection: Solvent resistant protective clothing
- Limitation and supervision of exposure into the environment

No further relevant information available.

Risk management measures

See Section 7 for additional information. No further relevant information available.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: Amber colored
Odor: Petroleum-like
Odor threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 105 - 199 °C (221 - 390 °F)

Flash point: 38 °C (100 °F)
 Flammability (solid, gaseous): Not applicable.
 Auto-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/

vapor mixtures are possible.

· Explosion limits:

Lower: 0.8 Vol % **Upper:** 6.0 Vol %

· Vapor pressure: Not determined.

• **Density at 20 °C (68 °F):** 0.83 g/cm³ (6.926 lbs/gal)

(Contd. on page 8)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 7)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Other information
 No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:

Avoid open flame, ignition sources, contact with incompatibile substances.

Possibility of hazardous reactions

Flammable.

Reacts with strong oxidizing agents.

Toxic fumes may be released if heated above the decomposition point.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hvdrocarbons

Nitrogen oxides (NOx)

Toxic metal compounds

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification: None.
- Primary irritant effect:
- on the skin: Based on available data, the classification criteria are not met.
- · on the eye: Based on available data, the classification criteria are not met.
- Subacute to chronic toxicity: May be fatal if swallowed and enters airways.

(Contd. on page 9)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 8)

- Additional toxicological information:
- Carcinogenic categories
- · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Probable Routes of Exposure

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- Repeated Dose Toxicity: Repeated exposures may result in skin and/or respiratory sensitivity.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 2, Repr. 2

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Suspected of causing cancer.
- · Reproductive toxicity Suspected of damaging fertility or the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure

Causes damage to the central nervous system through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- **Ecotoxical effects:**
- Remark: Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
- Additional ecological information:
- General notes: Do not allow product to reach ground water, water course or sewage system.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

(Contd. on page 10)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

(Contd. of page 9)

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

UN-Number

· DOT, ADR, IMDG, IATA UN1263

UN proper shipping name



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

DOT, IATA Paint related material

• ADR 1263 PAINT RELATED MATERIAL • IMDG PAINT RELATED MATERIAL

Transport hazard class(es)

DOT



Class 3 Flammable liquids

Label

ADR



· Class 3 (F1) Flammable liquids

Label

IMDG, IATA



· Class 3 Flammable liquids

· Label 3

Packing group

· DOT, ADR, IMDG, IATA

Environmental hazards:

· Marine pollutant: No

• Special precautions for user Warning: Flammable liquids

Danger code (Kemler):

(Contd. on page 11)

(Contd. of page 10)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

F-E,S-E

· EMS Number: · Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Code: E1 Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

 Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN1263, Paint related material, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

61789-51-3 Naphthenic acids, cobalt salts

· TSCA (Toxic Substances Control Act):

Some ingredients listed.

- Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

IARC (International Agency for Research on Cancer)

61789-51-3 Naphthenic acids, cobalt salts

2B

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· State Right to Know Listings

None of the ingredients is listed.

(Contd. on page 12)

Printing date 07/09/2015 Reviewed on 07/09/2015

Trade name: Waterlox Original Sealer/Finish

Canadian substance listings:

· Canadian Domestic Substances List (DSL)

Some ingredients listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

8052-41-3 Stoddard solvent

Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 07/09/2015 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com