



URETHANE

CRYSTAL CLEAR | SUPERIOR PROTECTION



Protect your wood project with the trusted,
go-to finish wood enthusiasts choose.

Easy to apply,
maintain
and restore

Crystal clear allows
the natural wood color
to shine through

Forms a rock-hard
finish for superior
protection

Available in
gloss, semi-gloss
and satin sheens



FAMILY
OWNED
SINCE 1910



Learn more at waterlox.com/urethane

Our URETHANE Formula

Our URETHANE formula is crystal clear and provides a rock-hard finish. Because there is no ambering with this product, the natural color of your wood floors, paneling, trim, cabinets, doors, bar tops and furniture shine through.

PRODUCT DETAILS:

- Use alone to provide a crystal clear protective finish or in conjunction with the Universal Tung Oil Sealer to provide a protective finish with an ambering effect.
- Unlike linseed oil-based polyurethanes, our URETHANE formula will not yellow over time.
- Excellent water resistance.
- Non-toxic when dry and fully cured.
- Hand made in Ohio by a 4th generation, family-owned company.
- Available in gloss, semi-gloss and satin sheens.
- Available in gallon, quart and 2 ounce sizes.

PRODUCT USES & TIPS:

- Use on interior wood surfaces including floors, windows, doors, cabinetry, woodwork, tables, furniture, bar tops, picture frames, and various woodworking projects where a rock-hard surface and no yellowing or ambering is desired.
- Can be used over oil paint and stain. Will not yellow over time. Excellent for lighter colored woods, like maple, and neutral stain colors like whites, grays and black.
- One quart of ORIGINAL SEALER or URETHANE finish covers 125 square feet per coat (500 square feet per coat for one gallon). One quart of the Universal Tung Oil Sealer covers 600-800 square feet per coat. No thinning required.
- Allow to dry for 24 hours. **Sanding with abrasive pads between coats is required for adhesion.** Use maroon pads (i.e.: surface preparation pad, a.k.a. SPP pads), a 100-grit screen, a 320-grit sandpaper, a 000 steel wool or other equivalent abrasive.

1 If desired, apply ONE OF THESE products to provide an ambering effect.

ORIGINAL SEALER &
SEMI-GLOSS FINISH

OR UNIVERSAL TUNG OIL SEALER

PRODUCT #:
TB 5284



PRODUCT #:
TB 1000



2 Apply one of these products to build a rock-hard finish.

URETHANE GLOSS FINISH

PRODUCT #: **TB 4252**
GLOSS LEVEL: **85°**

This product is a finish and can be used alone or over the Waterlox Universal Tung Oil Sealer (TB 1000).



URETHANE SEMI-GLOSS FINISH

PRODUCT #: **TB 5824**
GLOSS LEVEL: **70-80°**

This product is a finish and can be used alone or over the Waterlox Universal Tung Oil Sealer (TB 1000).



URETHANE SATIN FINISH

PRODUCT #: **TB 5930**
GLOSS LEVEL: **25-30°**

This product is a finish and can be used alone or over the Waterlox Universal Tung Oil Sealer (TB 1000).



Premium finishes since 1910.