

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** XL-89 Satin Urethane
- **Article number:** TB 5930
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Waterlox Coatings Corporation  
9808 Meech Avenue  
CLEVELAND, OH 44105  
(216) 641-4877
- **1.4 Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).  
The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H317, H351.



Skin Sens. 1 H317: May cause an allergic skin reaction.

Carc. 2 H351: Suspected of causing cancer.



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

R10: Flammable.

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 1)

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Stoddard solvent  
2-butanone oxime  
ethylbenzene

- **Hazard statements**

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H317, H351.

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

The following Precautionary Statements are applicable only to the OSHA GHS regulations and not the specific CLP regulation: P201, P202, P308+P313.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: **XL-89 Satin Urethane**

(Contd. of page 2)

P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P331 Do NOT induce vomiting.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

EUH208 Contains 2-butanone oxime. May produce an allergic reaction.

- **Hazard description:**

- **WHMIS-symbols:**

B3 - Combustible liquid

D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **HMIS Long Term Health Hazard Substances**

96-29-7	2-butanone oxime
100-41-4	ethylbenzene

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

(Contd. on page 4)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

		(Contd. of page 3)
CAS: 8052-41-3 EINECS: 232-489-3 Index number: 649-345-00-4	Stoddard solvent ☒ Xn R65 R10 ----- ☠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304	50-100%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene ☒ Xn R48/20-65; ☠ F R11 ----- ☠ Flam. Liq. 2, H225 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ☠ Acute Tox. 4, H332 Aquatic Chronic 3, H412	< 1%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0	2-butanone oxime ☒ Xn R21-40; ☒ Xi R41; ☒ Xi R43 Carc. Cat. 3 ----- ☠ Carc. 2, H351 ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H312; Skin Sens. 1, H317	< 1%
<p>· <b>Additional information:</b> For the listed ingredients, the identity and exact percentages are being withheld as a trade secret. For the wording of the listed risk phrases refer to section 16.</p>		

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

#### · **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

#### · **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

#### · **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

### · 4.2 Most important symptoms and effects, both acute and delayed

Headache

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

**Trade name: XL-89 Satin Urethane**

(Contd. of page 4)

Coughing  
Breathing difficulty  
Dizziness  
Nausea  
Disorientation

· **Hazards**

Danger of impaired breathing.  
Danger of convulsion.  
Danger of disturbed cardiac rhythm.  
Vapours may cause drowsiness and dizziness.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Medical supervision for at least 48 hours.  
If swallowed or in case of vomiting, danger of entering the lungs.  
Later observation for pneumonia and pulmonary oedema.  
If necessary oxygen respiration treatment.  
Monitor circulation, possible shock treatment.  
Treat skin and mucous membrane with antihistamine and corticoid preparations.  
Contains 2-butanone oxime. May produce an allergic reaction.

## SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Foam  
Fire-extinguishing powder  
Gaseous extinguishing agents  
Carbon dioxide  
Water haze or fog

· **For safety reasons unsuitable extinguishing agents:**

Water spray  
Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.  
Wear fully protective suit.

· **Additional information**

Eliminate all ignition sources if safe to do so.  
Cool endangered receptacles with water fog or haze.

## SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

**Trade name: XL-89 Satin Urethane**

(Contd. of page 5)

Keep away from ignition sources.

Protect from heat.

Particular danger of slipping on leaked/spilled product.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

· **6.3 Methods and material for containment and cleaning up:**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Allow to solidify. Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Emergency cooling must be available in case of nearby fire.

Keep respiratory protective device available.

Flammable gas-air mixtures may form in empty receptacles.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 7)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 6)

· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****8052-41-3 Stoddard solvent**

PEL (USA)	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit: 1800* mg/m <sup>3</sup> *15-min
TLV (USA)	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
EL (Canada)	Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 525 mg/m <sup>3</sup>

**100-41-4 ethylbenzene**

IOELV (EU)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin
PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

**96-29-7 2-butanone oxime**

WEEL (USA)	Long-term value: 10 ppm DSEN
------------	---------------------------------

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· **Ingredients with biological limit values:****100-41-4 ethylbenzene**

BEI (USA)	0,7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 8)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 7)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Suitable respiratory protective device recommended.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Body protection:** Solvent resistant protective clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

(Contd. on page 9)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 8)

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form: Liquid  
Colour: Amber coloured

· Odour: Petroleum-like

· Odour threshold: Not determined.

· pH-value: Not determined.

#### · Change in condition

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: 150 - 199 °C (302 - 390 °F)

· Flash point: 38 °C (100 °F)

· Flammability (solid, gaseous): Not applicable.

· Auto/Self-ignition temperature: Not determined.

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### · Explosion limits:

Lower: 0,6 Vol %

Upper: 0,8 Vol %

· Vapour pressure: Not determined.

· Density at 20 °C (68 °F): 0,88 g/cm<sup>3</sup> (7,344 lbs/gal)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

#### · Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

#### · 9.2 Other information

No further relevant information available.

(Contd. on page 10)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 9)

## SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
Avoid open flame, ignition sources, contact with incompatible substances.
- **10.3 Possibility of hazardous reactions**  
Flammable.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Develops readily flammable gases/fumes.  
Toxic fumes may be released if heated above the decomposition point.  
Reacts with strong oxidising agents.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **10.4 Conditions to avoid**  
Keep ignition sources away - Do not smoke.  
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Hydrocarbons  
Nitrogen oxides (NO<sub>x</sub>)

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect:**
- **on the skin:** Slight irritant effect on skin and mucous membranes.
- **on the eye:** Slight irritant effect on eyes.
- **Sensitisation:** Sensitising effect by skin contact is possible by prolonged exposure.
- **Subacute to chronic toxicity:** May be fatal if swallowed and enters airways.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Harmful  
Toxic and/or corrosive effects may be delayed up to 24 hours.
- **Repeated dose toxicity:**  
May cause damage to organs through prolonged or repeated exposure.  
Repeated exposures may result in skin and/or respiratory sensitivity.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**  
Carc. 2B  
Classification for the United States only.

(Contd. on page 11)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 10)

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The product contains materials that are harmful to the environment.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
-  Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).
- **DOT** Paint related material
- **ADR** 1263 PAINT RELATED MATERIAL
- **IMDG, IATA** PAINT RELATED MATERIAL

(Contd. on page 12)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 11)

## · 14.3 Transport hazard class(es)

## · DOT



· Class 3 Flammable liquids.  
· Label 3

## · ADR



· Class 3 (F1) Flammable liquids.  
· Label 3

## · IMDG, IATA



· Class 3 Flammable liquids.  
· Label 3  
· 14.4 Packing group  
· DOT, ADR, IMDG, IATA III  
· 14.5 Environmental hazards:  
· Marine pollutant: No  
· 14.6 Special precautions for user Warning: Flammable liquids.  
· Danger code (Kemler): 30  
· EMS Number: F-E, S-E  
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

## · Transport/Additional information:

## · ADR

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml  
· Transport category 3  
· Tunnel restriction code D/E

## · IMDG

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

· UN "Model Regulation":

UN1263, PAINT RELATED MATERIAL, 3, III (Contd. of page 12)

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

## · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

## · Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

## · TSCA (Toxic Substances Control Act):

All ingredients are listed.

## · Proposition 65 (California):

## · Chemicals known to cause cancer:

100-41-4 ethylbenzene

## · Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

## · Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

## · Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

## · Carcinogenic Categories

## · EPA (Environmental Protection Agency)

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

## · IARC (International Agency for Research on Cancer)

1330-20-7 xylene

3

100-41-4 ethylbenzene

2B

## · TLV (Threshold Limit Value established by ACGIH)

100-41-4 ethylbenzene

A3

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

## · Canada

## · Canadian Domestic Substances List (DSL)

All ingredients are listed.

## · Canadian Ingredient Disclosure list (limit 0.1%)

100-41-4 ethylbenzene

(Contd. on page 14)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

Trade name: XL-89 Satin Urethane

(Contd. of page 13)

<b>· Canadian Ingredient Disclosure list (limit 1%)</b>	
8052-41-3	Stoddard solvent

**· Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

<b>· Substances of very high concern (SVHC) according to REACH, Article 57</b>
None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H332 Harmful if inhaled.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

R10 Flammable.  
 R11 Highly flammable.  
 R21 Harmful in contact with skin.  
 R40 Limited evidence of a carcinogenic effect.  
 R41 Risk of serious damage to eyes.  
 R43 May cause sensitisation by skin contact.  
 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 R65 Harmful: may cause lung damage if swallowed.

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 WHMIS: Workplace Hazardous Materials Information System (Canada)  
 DNEL: Derived No-Effect Level (REACH)

(Contd. on page 15)

**Safety Data Sheet**  
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
OSHA GHS

Printing date 13.04.2015

Revision: 13.04.2015

**Trade name: XL-89 Satin Urethane**

(Contd. of page 14)

PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Carc. 2: Carcinogenicity, Hazard Category 2  
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

**Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)