



UNIVERSAL TUNG OIL SEALER

HIGH SOLIDS BASE COAT MADE WITH TUNG OIL



A universal base coat made for H2OLOX,
ORIGINAL, MARINE & URETHANE Finishes.

Easy buff-in
application that locks
out water

Used as a
replacement to our other
sealer products

Low odor,
low VOC and
easy to clean up

Use with our H2OLOX,
ORIGINAL, MARINE &
URETHANE finishes



FAMILY
OWNED
SINCE 1910



Learn more at waterlox.com/sealer

Our UNIVERSAL Tung Oil Sealer

A high solids base coat sealer made with Tung Oil. When used in conjunction with our H2OLOX®, ORIGINAL, MARINE and URETHANE finish products, your wood floors, cabinets, countertops, furniture and woodworking projects will receive a durable, rich, distinctive finish that is easy to maintain, low odor, low VOC and easy to clean up.

PRODUCT DETAILS:

- VOC compliant in all 50 states. Use as a sealer for H2OLOX. Can replace our existing sealer products (ORIGINAL, MARINE and VOC Compliant).
- Like all of our Tung Oil formulas, 90% of the resin portion of the formula is from renewable, natural resources.
- Formulated as a base coat sealer to be used in conjunction with our H2OLOX, ORIGINAL, MARINE and URETHANE finish products. Together, they create a waterproof barrier while forming a protective film that is durable against common household use and foot traffic.
- Non-toxic when dry and fully cured.
- Hand made in Ohio by a 4th generation, family-owned company.
- Available in gallon, quart, pint, half pint and 2 ounce sizes.

PRODUCT USES & TIPS:

- Use as a based coat on interior or exterior* wood surfaces including floors, windows, doors, cabinetry, woodwork, tables, furniture, bar tops, picture frames and various woodworking projects.
- Provides exceptional adhesion to oily, dense, exotic woods like teak, rosewood and ipe.
- One quart of sealer covers 600-800 square feet per coat. No thinning required.
- Allow to dry overnight before applying finish coats. Poor ventilation, high humidity or cool temperatures may increase dry times.
- Keep container closed when not in use and keep from freezing.

* Product contains no mold or mildewcides. One can be added if used on exterior projects.

- 1 First, apply this product to create a waterproof seal.

UNIVERSAL TUNG OIL SEALER

PRODUCT #: **TB 1000**

This product is a sealer and should be used under the Waterlox H2OLOX, Original, Marine and Urethane finish products.



- 2 Second, apply one of these products to build a protective and elastic finish.

H2OLOX FINISHES

PRODUCT #: **TB 2000, TB 2001, TB 2002 and TB 2003**



ORIGINAL FINISHES

PRODUCT #: **TB 5284, TB 3182 and TB 6044**



MARINE FINISHES

PRODUCT #: **TB 3940 and TB 6032**



URETHANE FINISHES

PRODUCT #: **TB 4252, TB 5824 and TB 5930**



Premium tung oil finishes since 1910.